



Move into a new age of preserved wood with Wolmanized EraWood™

In an era when consumers want environmentally sustainable products, natural appearance, low chemical content, low corrosivity, and effective coverage with paint and stain, without giving up performance...

Wolmanized EraWood™ decking, lumber & timbers – responsible science meets wood preservation

Wolmanized EraWood™ delivers all the performance of traditional pressure-treated wood with an EPA-registered carbon-based preservative. A proprietary stabilizer is included to minimize the effects of moisture and help prevent warping, twisting and cracking.

The preservative formulation has low impact; the wood it protects is GreenSpec®-listed, certified as a Green Approved product by NAHB Research Center, and has earned the Good Housekeeping Seal. Despite the low environmental impact of the wood, there is nothing gentle about its effectiveness. This wood is listed in AWPAs standards and backed by a lifetime limited warranty against fungal decay and termite damage.

This wood is intended for out-of-ground use, such as deck platforms & railings, stair treads & risers, beams & joists, fence boards, door & window molding & trim, soffit & fascia, and outdoor furniture.

Features

- Protected against termite damage and fungal decay by an EPA-registered carbon-based formulation
- Dual mold inhibitors help prevent mold growth
- Quality monitored by third-party inspection agency
- Lifetime limited warranty* against termites and decay fungi
- Suited for decking, rails, fence boards, and out-of-ground applications
- Corrosivity similar to that of untreated wood; can contact aluminum without fear of accelerated corrosion
- Can be painted or stained without discoloration from preservative
- No more effect on woodworking tools than untreated wood
- GreenSpec® listed; Green Approved product

*see reverse side



Building Tips

- Use only for out-of-ground applications.
- For a deck floor: if the wood is wet and heavy, butt boards together as some shrinkage will occur; if wood is dry and light, separate boards slightly (max. 1/8") to allow for future swelling.
- For 2" lumber, use 3 1/4" nails or 3" screws. For 5/4 decking, use 3" nails or 2 1/2" screws.
- Screws take longer to drive than nails, but hold boards securely and will allow for easier removal if necessary.

Recommended Hardware

- Moisture, salt, and other agents can cause metal corrosion, but Wolmanized EraWood™ is no more corrosive than untreated wood. Check with hardware manufacturer regarding specific uses. Observe building codes.
- Aluminum can be used in direct contact with this wood.

Maintenance Tips

- No maintenance is needed to renew resistance to fungi and termites. Wolmanized EraWood™ wood has a lifetime limited warranty against these organisms.
- For surface protection against moisture damage, spray or brush on an effective brand of water repellent as soon as your project is finished or, for large projects, as sections are completed.
- It helps to re-apply a topical water repellent every year or two.
- To revitalize a dingy appearance caused by dirt, mildew and mold, use a deck brightener to clean the wood.
- Check with the experts in the store's coatings department for recommendations on water repellent, stain, and cleaner.

Safety Information

This wood has been preserved by pressure-treatment with an EPA-registered pesticide to protect it from termite attack and fungal decay. Wood treated with any preservative should be used only where such protection is necessary or important.

In the treating process, the preservative penetrates deeply into the wood where it remains for many years. However, a small amount of chemical may migrate from preserved wood into surrounding soil over time and may also be dislodged from the wood surface upon contact with skin. Precautions should be taken when handling the preserved wood. Many of these precautions also apply to untreated wood and other building materials.

For Use Site Precautions and other helpful information, visit

www.WolmanizedWood.com/EraWood

Handling Precautions

- Dispose of treated wood by ordinary trash collection. TREATED WOOD SHOULD NOT BE BURNED in open fires or in stoves, fireplaces or residential boilers.
- When sawing, sanding, and machining wood, wear a dust mask. Avoid frequent or prolonged inhalation of sawdust from wood, treated or untreated. Whenever possible, these operations should be performed outdoors.
- Wear gloves when working with wood. Wear goggles to protect eyes from flying particles. Use proper techniques when lifting.
- After working with wood, and before eating, drinking, toileting, or using tobacco products, wash exposed skin areas thoroughly.
- Because preservatives or sawdust may accumulate on clothes, they should be laundered before reuse. Wash work clothes separately from other household clothing.

Lifetime Limited Warranty

When used in an out-of-ground application and in conjunction with a residential or agricultural structure located in the United States of America, then subject to the conditions contained in this Warranty, your Wolmanized EraWood™ lumber is warranted against such damage by termites or fungal decay as would make the lumber structurally unfit for the applications for which it was intended.

This warranty is good from the date of purchase for as long as you own the property on which your new Wolmanized EraWood™ lumber structures are built. This warranty is applicable to the original purchaser and property owner only, and is not transferable to any other property owner. The original consumer purchaser will be entitled to be reimbursed for the actual, reasonable cost of new Wolmanized EraWood™ lumber which is purchased to replace wood which was made structurally unfit by damage due to termites or fungal decay. To obtain the necessary prior approval for, and make arrangements for, this reimbursement, the original owner must send sufficient warranty labels, along with the original purchase invoice, showing that a sufficient amount of Wolmanized EraWood™ lumber was originally purchased to cover the number of board feet claimed to be damaged, to the Warrantor, at:

**Wolmanized EraWood™ Lumber
Warranty Claim Administrator
Arch Treatment Technologies, Inc.
5660 New Northside Dr., Suite 1100
Atlanta, GA 30328**

When making any warranty claim you may be required to send photographs and pieces of damaged wood. In addition, at the Warrantor's request, the Warrantor and its representatives and agents must be permitted to inspect and test the damaged structure.

Warrantor shall not be liable hereunder for damage to Wolmanized EraWood™ lumber resulting from any cause other than termites or fungal decay, or for any damage to wood which has been used in a structure outside of the U.S.; used in the ground or in fresh or salt water; used for commercial or industrial projects; used in commonly owned property and structures such as condominiums; or used for an application or in a way that is not consistent with the end use identified on its original label or stamp.

Warrantor shall not be liable for any installation, repair, construction, labor or similar costs, or for any costs or damage which may be associated with the natural characteristic of some wood to split, crack, warp, or twist. To the maximum extent permitted by applicable law, in no event shall Warrantor be responsible for any direct, indirect, incidental, consequential or financial damages or expenses of any kind whatsoever, howsoever caused (whether or not due to any deficiency or negligence in manufacturing, and whether or not relating to loss, damage, death or injury) arising out of or relating to your purchase or use of Wolmanized EraWood™ lumber.

For hem-fir, Douglas fir, and western hemlock of any dimension, and for other species with a nominal thickness greater than six inches, this warranty is null and void unless all cuts and injuries in the treated wood, including but not limited to cut ends and bore holes, were properly coated at the time of construction with two saturating brush coats of a suitable wood preservative. Suitable wood preservatives contain a minimum of 0.675% copper as oxine copper (copper-8 or copper-8-quinolinolate), 1% copper as copper naphthenate, or 2% zinc as zinc naphthenate. Proof of purchase of the preservative is also required. Hem-fir, Douglas fir, and western hemlock are covered by this warranty only when used in the states of Alaska, Arizona, California, Colorado, Idaho, Montana, Nevada, New Mexico, Oregon, Utah, Washington, Wyoming, and Hawaii (except for unincised decking which is specifically not warranted by Warrantor in Hawaii).

BY PURCHASING WOLMANIZED ERAWOOD™ LUMBER, YOU ACCEPT THE TERMS OF THIS WARRANTY AND HEREBY ACKNOWLEDGE AND AGREE THAT THIS LIMITED WARRANTY IS THE ONLY WARRANTY MADE BY WARRANTOR WITH RESPECT TO WOLMANIZED ERAWOOD™ LUMBER AND REPLACES ALL OTHER REPRESENTATIONS, WARRANTIES, GUARANTEES, PROMISES OR COMMITMENTS, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND ANY OTHER IMPLIED WARRANTIES OTHERWISE ARISING FROM THE COURSE OF DEALING OR USAGE OF TRADE OR ADVERTISING,

In no event will Warrantor be liable for any incidental, special, indirect, multiple, punitive or consequential damages resulting from any defect in any Wolmanized EraWood™ lumber, including but not limited to personal injury, damage to property or lost profits. Only the Warrantor is liable under this Limited Warranty and the directors, officers, employees and agents shall have no liability of any kind to you or to others with respect to your purchase or use of Wolmanized EraWood™ lumber.